

## IN THE CLAIMS:

1.- 18 (canceled)

19. (currently amended) ~~The railway crossing of claim 12,~~ A railway crossing, comprising:  
a plate having a plurality of plate segments and a pocket formed in the plate segments  
that defines a crossing angle, the pocket having a plurality of protrusions formed therein;  
a pair of continuous long beams, each having a base seated in the pocket of the plate;  
a pair of divided beams, each having three separate, discontinuous segments, and each of  
the segments having a base seated in the pocket in the plate and positioned at the crossing angle  
with respect to the long beams such that each of the segments abuts at least one of the long  
beams; and  
at least one recess formed in each of the bases of the long beams and in each of the bases  
of the segments of the divided beams, the recesses being complementary in shape to the  
protrusions in the pocket, such that engagement of the recesses by the protrusions resists  
movement of the long and divided beams along lengths thereof with respect to the plate;  
fasteners for securing the long beams and the divided beams in the pocket of the plate;  
and  
wherein each of the fasteners comprises a rail brace assembly having a wedge brace  
joined to the plate, a clip joined to the wedge brace, and a wedge mounted between the wedge  
brace, the clip, and one of the long beams and the divided beams, such that the wedge prevents  
pull-apart of the plate, the long beams, and the divided beams due to thermal forces, mechanical  
forces, and surface discontinuities.

20. (previously presented) A railway crossing, comprising:  
a plate;  
a plurality of long beams mounted to the plate and having a longitudinal length and a  
lateral width that is transverse thereto;  
a plurality of divided beams, each having a plurality of segments, mounted to the plate  
and positioned at a crossing angle with respect to the long beams, and each of the segments  
having a longitudinal length and a lateral width that is transverse thereto; [[and]]

fasteners for securing the long beams and the divided beams to the plate and resisting both vertical movement and lateral horizontal movement of the long and divided beams with respect to the plate, each of the fasteners comprising a rail brace assembly having a wedge brace joined to the plate, a clip joined to the wedge brace, and a wedge mounted between the wedge brace, the clip, and one of the long beams and the divided beams, such that the wedge prevents pull-apart of the plate, the long beams, and the divided beams due to thermal forces, mechanical forces, and surface discontinuities; and

the wedge brace has a receptacle formed therein with a tapered surface, each of the long beams and the segments of the divided beams has a tapered side wall, the wedge has a tapered knob that is complementary in shape to the receptacle and its tapered surface for engagement therewith, and the wedge has a tapered surface opposite the tapered knob that is complementary in shape to the tapered side walls for engagement therewith.

21. (canceled)

22. (original) The railway crossing of claim 20, wherein the plate has a pocket formed therein for receiving the long beams and the divided beams.

23. (original) The railway crossing of claim 22, wherein the pocket has a plurality of protrusions formed therein, and each of the long beams and each of the divided beams has at least one recess that is complementary in shape to the protrusions in the pocket, such that engagement of the recesses by the protrusions resists movement of the long and divided beams along the longitudinal lengths thereof with respect to the plate.

24. (original) The railway crossing of claim 20, wherein the longitudinal length of each of the segments of the divided beams is shorter than the longitudinal length of the long beams.

25. (original) The railway crossing of claim 20, wherein the crossing angle is in the range of 40 degrees to 90 degrees.

26. (original) The railway crossing of claim 20, wherein the segments of each of the divided beams comprise a pair of outer segments located outside of the long beams and in abutment with one of the long beams, and an inner segment located between the long beams and in abutment with all of the long beams.

27. (original) The railway crossing of claim 26, wherein the longitudinal length of each of the inner segments is shorter than the longitudinal length of either of the outer segments, and wherein the outer segments are equal in length.

28. (original) The railway crossing of claim 26, wherein the inner segments are reversible such that the inner segment of one of the divided beams may be interchangeably positioned with the inner segment of the other of the divided beams, and wherein the outer segments are reversible such that the outer segments of said one of the divided beams may be interchangeably positioned with the outer segments of said the other of the divided beams.

29. (original) The railway crossing of claim 20, wherein the plate comprises a plurality of plate segments.